TE-100 SERIES

Kemco's pioneering 99.7% efficient direct contact water heater, the TE-100 delivers hot water on demand. Each unit is custom designed to meet the customer's individual requirements, heating large volumes of water from an incoming cold temperature to a final hot usage temperature, in a single pass. Heated water, ready for use, is then stored in an open hot water tank.





FEATURES

- On-Demand Hot Water
- Stainless Steel Construction
- Non-Pressure Vessel
- Heating Flows to 500 gpm
- Temperature as High as 199°F
- NSF-Certified Models
- Insurance-Rated Gas Trains
- PLC-Based System Control Panel
- · Media Tower Manway
- No Operator Certification Required
- Low NOx Available

APPLICATIONS

Processing Hot Water

Heating Water for "Water to Water" Heat Exchanger Applications

	Heater Size (mbtu)	Water Heating Capacity at ΔT 100°F (gph)	Dimensions (D x H)	Weight Empty (lbs)	Weight Flooded (lbs)	Water Inlet	Water Outlet	Gas Inlet	Min. Typical Connected Load (FLA)
	1.2	1,440	25 ½" x 9'	1,000	1,450	1" - 2"	2"	1 ½"	5.0
	2.0	2,400	30" x 10'	2,400	3,100	1 ¼" - 2"	3"	1 ½"	5.0
ECH ICALIONS	3.0	3,600	30" x 10'	2,400	3,100	1 ½" - 2"	3"	1 ½"	6.5
	4.5	5,400	42" x 10'	2,650	3,850	2" - 2 ½"	4"	2"	6.5
	5.5	6,600	42" x 10'	3,000	4,250	2" - 3"	4"	2"	8.0
	7.0	8,400	54" x 11'	3,200	5,800	2 ½" - 3"	4"	2"	14.5
	9.0	10,800	54" x 11'	3,200	5,800	3"	4"	2"	17.5
	10.0	12,000	54" x 11'	3,200	5,800	3" - 4"	4" - 6"	2 ½"	24.5
	12.0	14,400	69" x 11'	4,900	9,100	3" - 4"	6"	3"	24.5
5	15.0	18,000	76" x 11'	5,100	10,200	4"	6"	3"	24.5
	18.0	21,600	84" x 11'	6,000	12,200	4"	6"	3"	43.5
	21.0	25,200	84" x 11'	6,000	12,200	4"	6"	3"	55.5
	25.0	30,000	96" x 12'	7,000	15,100	4"	8"	3"	68.5